

Proposed Terms:

- Contract Term: Spot to 5 years
- Annual quantity: Up to 300,000 tons in 2025
- Delivery Terms : FOB Vietnam
- Delivery size: 30,000 tons +/- 10% in buyer's option
- Loading Rate: 5,000 ton per WWD SSHINC

Our offer terms & Specifications

ISO Standard Quality Parameters RHP		
Parameter	Units	Limit
Sampling		
Additives / Binders	%wt	None
Sample Preparation		
Physical Parameters		
Temperature	deg C	60
Fines ≤3.15 mm (round-hole sieves)	%wt, arb	≤ 2%
Diameter	mm, arb	6 to 10
Bulk (apparent) Density	kg/m3, arb	> 600
NCV at constant pressure	GJ/MT, arb	> 14.0
Ash	% wt, db	≤ 15%
Ash Deformation Temp	deg C	> 1500
Durability	%wt, arb	97% - 99%
Water content	% wt, arb	≤ 10%
Elementary Composition		
N	%wt, db	≤ 1.0%
S	%wt, db	≤ 0.2%
Cl	%wt, db	≤ 0.12%
Major & Minor Metals		
As	mg/kg, db	≤ 2
Cd	mg/kg, db	≤ 1
Cr	mg/kg, db	≤ 15
Cu	mg/kg, db	≤ 20
Pb	mg/kg, db	≤ 20
Zn	mg/kg, db	≤ 200